



SC7

回转驱动性能参数 Slewing Drive Performance Parameters

减速比	Gear Ratio	71:1	
输出转速	Output Speed	0.042rpm	
输出力矩	Output Torque	937.2N.m	691.6 lbf.ft
最大倾覆力矩	Tilting Moment (max.)	13.5 kN.m	9.96×10 ³ lbf.ft
保持力矩	Holding Torque	10.4 kN.m	7.67×10 ³ lbf.ft
轴向静载荷	Static Axial Load Rating	133 kN	30×10 ³ lbf
径向静载荷	Static Radial Load Rating	53 kN	11.9×10 ³ lbf
机械效率	Mechanical Efficiency	40%	
自锁性	Self-locking	可靠的静态自锁Reliable static self-locking	
精度	Precision	≤0.2°	
防护等级	IP Class	IP65	

VH7

回转驱动性能参数 Slewing Drive Performance Parameters

减速比	Gear Ratio	60:1	
输出转速	Output Speed	0.05rpm	
输出力矩	Output Torque	2100N.m	1549.8 lbf.ft
最大倾覆力矩	Tilting Moment (max.)	10 kN.m	7.38×10 ³ lbf.ft
保持力矩	Holding Torque	42 kN.m	31×10 ³ lbf.ft
轴向静载荷	Static Axial Load Rating	100 kN	22.5×10 ³ lbf
径向静载荷	Static Radial Load Rating	65 kN	14.6×10 ³ lbf
机械效率	Mechanical Efficiency	35%	
自锁性	Self-locking	可靠的静态自锁Reliable static self-locking	
精度	Precision	≤0.2°	
防护等级	IP Class	IP65	